

构造表

芯数	导体			护套 标准厚度 (mm)	成品外径 约 (mm)	概算质量(kg/km)			
	公称截面积 (mm ²)	构 成 (根/mm)	外 径 (mm)			E V	V V	E E	EM EE / F
2	0.2	7 / 0.18	0.54	1.3	5.5	35	35	30	35
3				1.3	5.5	40	40	35	40
4				1.3	6.0	45	45	35	45
5				1.3	6.0	50	50	40	50
6				1.3	6.5	55	55	45	55
7				1.3	6.5	55	60	50	55
10				1.3	7.5	70	70	60	70
15				1.3	8.0	85	90	75	85
20				1.3	9.0	105	110	95	105
30				1.3	10.0	140	150	125	140
40				1.3	11.0	170	180	155	170
50				1.3	13.0	205	215	185	205
2	0.3	12 / 0.18	0.72	1.3	6.0	45	40	35	45
3				1.3	6.0	50	50	40	50
4				1.3	6.5	55	55	50	55
5				1.3	7.0	65	65	55	65
6				1.3	7.5	70	75	60	70
7				1.3	7.5	75	75	65	75
10				1.3	8.5	90	95	80	90
15				1.3	9.5	120	130	110	120
20				1.3	10.0	150	155	135	150
30				1.3	12.0	200	210	185	200
40				1.3	13.0	250	265	230	250
50				1.3	14.0	295	320	275	295
2	0.5	20 / 0.18	0.93	1.3	7.0	55	55	45	55
3				1.3	7.0	65	65	55	65
4				1.3	7.5	75	75	65	75
5				1.3	8.0	85	90	75	85
6				1.3	8.5	95	100	85	95
7				1.3	8.5	100	110	90	100
10				1.3	10.0	130	140	120	130
15				1.3	11.0	175	185	160	175
20				1.3	13.0	215	235	200	215
30				1.3	15.0	300	320	275	300
40				1.3	16.0	375	405	350	375
50				1.4	18.0	460	500	435	460
2	0.75	30 / 0.18	1.14	1.3	7.5	70	70	60	70
3				1.3	8.0	80	85	70	80
4				1.3	8.5	95	100	85	95
5				1.3	9.5	115	120	100	115
6				1.3	10.0	130	135	115	130
7				1.3	10.0	135	145	120	135
10				1.3	11.0	180	190	160	180
15				1.3	13.0	240	255	220	240
20				1.3	15.0	300	325	275	300
30				1.4	18.0	420	425	395	425
40				1.5	20.0	550	605	520	550
50				1.6	22.0	685	750	650	685
2	0.9	7 / 0.4	1.2	1.3	7.5	70	75	65	70
3				1.3	8.0	85	90	75	85
4				1.3	8.5	100	105	90	100
5				1.3	9.5	120	125	105	120
6				1.3	10.0	135	145	125	135
7				1.3	10.0	145	155	130	145
10				1.3	12.0	190	205	175	190
15				1.3	13.0	255	280	245	255
20				1.3	15.0	320	350	305	320
30				1.4	18.0	450	500	435	450
40				1.5	20.0	590	655	570	590
50				1.6	23.0	755	825	720	755
2	1.25	7 / 0.45	1.35	1.3	8.5	85	90	75	85
3				1.3	9.0	100	110	95	100
4				1.3	9.5	125	135	115	125
5				1.3	10.0	140	150	130	140
6				1.3	11.0	165	175	150	165
7				1.3	11.0	175	190	160	175
10				1.3	13.0	230	250	215	230
15				1.3	15.0	315	350	300	315
20				1.3	17.0	395	435	370	395
30				1.5	20.0	575	635	550	575
40				1.6	23.0	755	830	725	755
50				1.7	26.0	955	1050	910	955
2	2.0	37 / 0.26	1.83	1.3	9.5	115	125	105	115
3				1.3	10.0	145	150	130	145
4				1.3	11.0	175	180	160	175
5				1.3	12.0	200	210	180	200
6				1.3	12.0	230	245	215	230
7				1.3	12.0	250	265	230	250
10				1.3	15.0	335	355	315	335
15				1.4	18.0	475	510	450	475
20				1.5	20.0	625	670	595	625
30				1.6	24.0	900	970	860	900

注) 成品外径及概算质量是指编织屏蔽规格的产品。